



Product Service

Attestation of Conformity

No. N8A 17 10 77716 128

Holder of Certificate: SHENZHEN MOSO ELECTRONICS
TECHNOLOGY CO., LTD

No. 1061, Songbai Road, Xili
Nanshan District

518108 Shenzhen City, Guangdong Province
PEOPLE'S REPUBLIC OF CHINA

Product: Power supplies
(LED Driver)

Model(s): LSV-035B012; LSV-035B024; LSV-035B036;
LSV-035B048; LSV-050B012; LSV-050B024;
LSV-050B036; LSV-050B048

Parameters:

Rated Input Voltage :	100-277VAC
Rated Frequency :	50/60Hz
Rated Input Current :	See page 2 for details
Rated Output :	See page 2 for details
Protection against Electric Shock :	Class I; SELV
Degree of Protection :	IP67
Method of Installation :	Independent
Type of Output :	Constant voltage type
ta; tc :	ta: 60°C; tc: 85°C

Tested according to: EN 61347-2-13:2014/A1:2017
EN 61347-1:2015
EN 62493:2015

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 681401797901

Date, 2017-11-07

(Taylor Yao)



After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity
No. N8A 17 10 77716 128

Model	Rated Input Current (A)	U _{rated} (VDC)	Output Current (A)	P _{rated} (W)
LSV-035B012	Max. 0.50	12	Max. 2.90	Max. 35
LSV-035B024	Max. 0.50	24	Max. 1.46	Max. 35
LSV-035B036	Max. 0.50	36	Max. 0.97	Max. 35
LSV-035B048	Max. 0.50	48	Max. 0.73	Max. 35
LSV-050B012	Max. 0.80	12	Max. 4.17	Max. 50
LSV-050B024	Max. 0.80	24	Max. 2.08	Max. 50
LSV-050B036	Max. 0.80	36	Max. 1.39	Max. 50
LSV-050B048	Max. 0.80	48	Max. 1.04	Max. 50