



A P P R O V A L S ®

Certificate of Suitability

Certificate No.: SAA220460

Certificate Holder: Shenzhen Moso Electronics Technology Co.,Ltd
No. 1061, Songbai Road, Xili,
Nanshan District, 518108 Shenzhen City,
Guangdong Province
P.R. China

Regulatory Definition: Non-Declared

Product Description: LED Driver (Independent, Constant Current, Dimmable)

Standard/s: AS 61347.2.13:2018
AS/NZS 61347.1:2016 Inc A1

Condition/s: For use with LED lighting equipment only.
For Industrial use only.
Output circuits must not be accessible after installation.

Approval Marks: SAA220460

Initial Issue Date: 19 May 2022

Expiry Date: 19 May 2027

R.A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.



For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au

Issued: 19-05-22 220460
Page 1 of 2



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
X6-320M143	MOSO	Input: 100-240Vac or 100-277Vac or 200-240Vac, 50/60Hz, Max 4.2A Output: 72-143Vdc, Max Uout 160Vdc, 0.32-3.20A, Max 320W IP67, ta: 60°C (for 200-240Vac or 200-277Vac), tc: 90°C, Class I, Do Not Cover
X6-320M143A12	MOSO	Input: 100-240Vac or 100-277Vac or 200-240Vac, 50/60Hz, Max 4.2A Output: 72-143Vdc, Max Uout 160Vdc, 0.32-3.20A, Max 320W IP67, ta: 60°C (for 200-240Vac or 200-277Vac), tc: 90°C, Class I, Do Not Cover
X6-320V143	MOSO	Input: 100-240Vac or 100-277Vac or 200-240Vac, 50/60Hz, Max 4.2A Output: 72-143Vdc, Max Uout 160Vdc, 1.6-3.20A, Max 320W IP67, ta: 60°C (for 200-240Vac or 200-277Vac), tc: 90°C, Class I, Do Not Cover
X6-320M230	MOSO	Input: 100-240Vac or 100-277Vac or 200-240Vac, 50/60Hz, Max 4.2A Output: 115-230Vdc, Max Uout 260Vdc, 0.21-2.1A, Max 320W IP67, ta: 60°C (for 200-240Vac or 200-277Vac), tc: 90°C, Class I, Do Not Cover
X6-320M230A12	MOSO	Input: 100-240Vac or 100-277Vac or 200-240Vac, 50/60Hz, Max 4.2A Output: 115-230Vdc, Max Uout 260Vdc, 0.21-2.1A, Max 320W IP67, ta: 60°C (for 200-240Vac or 200-277Vac), tc: 90°C, Class I, Do Not Cover
X6-320V230	MOSO	Input: 100-240Vac or 100-277Vac or 200-240Vac, 50/60Hz, Max 4.2A Output: 115-230Vdc, Max Uout 260Vdc, 1.05-2.1A, Max 320W IP67, ta: 60°C (for 200-240Vac or 200-277Vac), tc: 90°C, Class I, Do Not Cover
X6-320M457	MOSO	Input: 100-240Vac or 100-277Vac or 200-240Vac, 50/60Hz, Max 4.2A Output: 228-457Vdc, Max Uout 480Vdc, 0.11-1.1A, Max 320W IP67, ta: 60°C (for 200-240Vac or 200-277Vac), tc: 90°C, Class I, Do Not Cover
X6-320M457A12	MOSO	Input: 100-240Vac or 100-277Vac or 200-240Vac, 50/60Hz, Max 4.2A Output: 228-457Vdc, Max Uout 480Vdc, 0.11-1.1A, Max 320W IP67, ta: 60°C (for 200-240Vac or 200-277Vac), tc: 90°C, Class I, Do Not Cover
X6-320V457	MOSO	Input: 100-240Vac or 100-277Vac or 200-240Vac, 50/60Hz, Max 4.2A Output: 228-457Vdc, Max Uout 480Vdc, 0.55-1.1A, Max 320W IP67, ta: 60°C (for 200-240Vac or 200-277Vac), tc: 90°C, Class I, Do Not Cover

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated in this certificate complies with standard/s listed.



For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au

Issued: 19-05-22 220460
Page 2 of 2